

Tubi Sezione Tonda 304/316

- Tubi a sezione **tonda elettrouniti saldati HF** secondo norme DIN 2463 ASTM A554.
- Tubi a sezione **tonda elettrouniti saldati TIG** secondo norme DIN 17457/17455 ASTM 778.
- Lunghezza commerciale mm 6000. Massa lineica convenzionale kg/mtl.

Tabella da 6 mm a 35 mm

Dimensioni		Sp = Spessori mm (Kg/m)				
mm Est.	Pollici	1,00	1,20	1,50	2,00	3,00
6,0		0,13	\	\	\	\
8,0		0,18	\	0,24	\	\
10,0	1/8"	0,23	\	0,32	\	\
12,0		0,28	\	0,39	0,50	\
13,0	1/4"	0,30	\	0,43	0,55	\
14,0		0,33	\	0,47	0,60	\
15,0		0,35	0,41	0,51	0,65	\
16,0		0,38	0,44	0,54	0,70	\
17,2	3/8"	0,41	0,48	0,59	0,76	1,07
18,0		0,43	0,50	0,62	0,80	\
19,1		0,45	0,54	0,66	0,85	\
20,0		0,48	0,56	0,69	0,90	1,28
21,3	1/2"	0,51	0,60	0,74	0,97	1,37
22,0		0,53	0,62	0,77	1,00	1,43
23,0		0,55	0,66	0,81	1,05	1,50
25,0		0,60	0,72	0,88	1,15	1,65
25,4		0,61	0,73	0,90	1,17	1,68
26,9	3/4"	0,65	0,77	0,95	1,25	1,80
28,0		0,68	0,81	1,00	1,30	1,88
30,0		0,73	0,87	1,07	1,40	2,03
32,0		0,78	0,93	1,15	1,50	2,18
33,7	1"	0,82	0,98	1,21	1,59	2,31
34,0		0,83	0,99	1,22	1,60	2,33
35,0		0,85	1,02	1,26	1,65	2,40

VERGALLI ACCIAI srl

Via Amendola, 18 Felegara 43040 (Pr) - Tel. + 39.0525.431675 - Fax +39.0525.430788

web: www.vergalliaccai.it - e-mail: vendite@vergalliaccai.it



Tabella da 38,1 mm a 45 mm

Dimensioni		Sp = Spessori mm (Kg/m)				
mm Est.	Pollici	1,00	1,20	1,50	2,00	3,00
38,1		0,93	1,11	1,37	1,81	2,64
40,0		0,98	1,17	1,45	1,90	2,78
42,4	1 1/4"	1,04	1,24	1,54	2,02	2,96
43,0		\	1,26	1,56	2,05	3,00
44,5		\	1,30	1,62	2,13	3,12
45,0		\	1,32	1,63	2,15	3,16

Tabella da 48,3 mm a 114,3 mm

Dimensioni		Sp = Spessori mm (Kg/m)					
mm Est.	Pollici	1,20	1,50	2,00	3,00	4,00	5,00
48,3	1 1/2"	1,42	1,76	2,32	3,40	4,44	\
50,0		1,47	1,82	2,40	3,53	4,61	\
50,8		1,49	1,85	2,44	3,59	4,69	\
52,0		1,53	1,90	2,50	3,68	4,81	\
54,0		1,59	1,97	2,60	3,83	5,01	\
57,0		1,68	2,08	2,75	4,06	5,31	\
60,3	2"	1,78	2,21	2,92	4,30	5,64	\
63,5		\	2,33	3,08	4,54	5,96	\
70,0		\	2,57	3,41	5,03	6,61	\
76,1	2 1/2"	\	2,80	3,71	5,49	7,22	\
80,0		\	2,95	3,91	5,78	7,61	\
84,0		\	3,10	4,11	6,08	8,01	\
85,0		\	3,14	4,16	6,16	8,11	\
88,9	3"	\	3,28	4,35	6,45	8,50	\
101,6	3 1/2"	\	3,76	4,99	7,41	9,78	\
104,0		\	3,85	5,11	7,59	10,02	\
108,0		\	4,00	5,31	7,89	10,42	\
114,3	4"	\	4,24	5,62	8,36	11,05	13,68

VERGALLI ACCIAI srl

Via Amendola, 18 Felegara 43040 (Pr) - Tel. + 39.0525.431675 - Fax +39.0525.430788

web: www.vergalliaccai.it - e-mail: vendite@vergalliaccai.it

Tabella da 129 mm a 355,6 mm

Dimensioni		Sp = Spessori mm (Kg/m)					
mm Est.	Pollici	1,20	1,50	2,00	3,00	4,00	5,00
129,0		\	4,79	6,36	9,47	12,52	15,52
139,7	5"	\	5,19	6,90	10,27	13,59	16,86
154,0		\	5,73	7,61	11,34	15,02	18,65
168,3	6"	\	6,27	8,33	12,42	16,46	20,45
204,0		\	\	10,12	15,10	20,03	24,91
219,1	8"	\	\	10,87	16,23	21,54	26,81
254,0		\	\	12,62	18,86	25,04	31,17
273,0	10"	\	\	13,57	20,28	26,94	33,55
306,0		\	\	15,22	22,76	30,25	37,69
323,9	12"	\	\	16,12	24,11	32,04	39,93
355,6		\	\	17,71	26,49	35,22	43,90
406,4			\	20,25	30,30	40,30	50,26



VERGALLI ACCIAI srl

Via Amendola, 18 Felegara 43040 (Pr) - **Tel.** + 39.0525.431675 - **Fax** +39.0525.430788

web: www.vergalliaccai.it - **e-mail:** vendite@vergalliaccai.it